

# Synthetic Designer Caster; WAVE

## WVX-P-25 Swivel casters

	Wheel diameter	Wheel width	Total height	Plate dimensions	Bolt hole spacing	Bolt hole diameter	Offset	Load capacity
WVX-101K-P-25	100	32	138	90 × 66	75 × 45-61 × 51	8.5	38	100(980)
WVX-126K-P-25	125	32	163	90 × 66	75 × 45-61 × 51	8.5	40	110(1070)

## WVX-FI-P-25 Swivel casters

	Wheel diameter	Wheel width	Total height	Plate dimensions	Bolt hole spacing	Bolt hole diameter	Offset	Load capacity
WVX-101K-FI-P-25	100	32	138	90 × 66	75 × 45-61 × 51	8.5	38	100(980)
WVX-126K-FI-P-25	125	32	163	90 × 66	75 × 45-61 × 51	8.5	40	110(1070)

## WVX Bolt hole fitting

	Wheel diameter	Wheel width	Total height	Plate dimensions	Bolt hole diameter	Offset	Load capacity
WVX-101K	100	32	135	55	8.5	38	100(980)
WVX-126K	125	32	160	55	8.5	40	110(1070)

## WVX-FI Bolt hole fitting

	Wheel diameter	Wheel width	Total height	Plate dimensions	Bolt hole diameter	Offset	Load capacity
WVX-101K-FI	100	32	135	55	8.5	38	100(980)
WVX-126K-FI	125	32	160	55	8.5	40	110(1070)

## WVX-GS Threaded stem fitting

	Wheel diameter	Wheel width	Total height	Stem size	Offset	Load capacity
WVX-101K-GS10	100	32	135	M10 × 20	38	100(980)
WVX-126K-GS12	125	32	160	M12 × 20	40	110(1070)

## WVX-FI-GS Threaded stem fitting

	Wheel diameter	Wheel width	Total height	Stem size	Offset	Load capacity
WVX-101K-FI-GS10	100	32	135	M10 × 20	38	100(980)
WVX-126K-FI-GS12	125	32	160	M12 × 20	40	110(1070)