



Platform Truck (with Folding/Fixed Handle, Flat)

Steel/Aluminium

Knockdown type - Most of our products come in knock-down form; user assembly required. Ask us for details when preassembled product is desired.



Stainless Steel

Single Ended with Folding Handle

SA-SUS S type

Load capacity	150 kg
Platform size	440 x 740 mm
Usable size	440 x 653 mm
Suitable caster	SW/SWUW POTH/PO
Platform height	160 mm 160 mm
Handle height	880 mm 880 mm
Empty weight	16.5 kg 16.1 kg

MA-SUS M type

Load capacity	300 kg
Platform size	560 x 860 mm
Usable size	560 x 773 mm
Suitable caster	SW/SWUW POTH/PO
Platform height	205 mm 205 mm
Handle height	880 mm 880 mm
Empty weight	25.0 kg 23.8 kg



SA-SUS

Single Ended with Fixed Handle

SB-SUS S type

Load capacity	150 kg
Platform size	440 x 740 mm
Usable size	440 x 680 mm
Suitable caster	SW/SWUW POTH/PO
Platform height	160 mm 160 mm
Handle height	860 mm 860 mm
Empty weight	15.0 kg 14.6 kg

MB-SUS M type

Load capacity	300 kg
Platform size	560 x 860 mm
Usable size	560 x 798 mm
Suitable caster	SW/SWUW POTH/PO
Platform height	205 mm 205 mm
Handle height	860 mm 860 mm
Empty weight	24.0 kg 22.8 kg



MB-SUS-POTH (Option)

Double Ended

SC-SUS S type

Load capacity	150 kg
Platform size	440 x 740 mm
Usable size	440 x 620 mm
Suitable caster	SW/SWUW POTH/PO
Platform height	160 mm 160 mm
Handle height	860 mm 860 mm
Empty weight	16.5 kg 16.1 kg

MC-SUS M type

Load capacity	300 kg
Platform size	560 x 860 mm
Usable size	560 x 736 mm
Suitable caster	SW/SWUW POTH/PO
Platform height	205 mm 205 mm
Handle height	860 mm 860 mm
Empty weight	27.0 kg 25.8 kg



MC-SUS-PO (Option)

Suitable Casters (with Radial ball bearing except PO)

Standard	SW	Stainless steel caster with SW wheel	Option	POTH	Stainless steel caster with POTH wheels (Wheel center: Nylon 6)	Option	PO	Stainless steel caster with PO wheels	Option	SWUW	Stainless steel caster with SWUW wheels
		Swivel			Swivel			Swivel			Swivel
		Fixed			Fixed			Fixed			Fixed
S type		SUNJ-100SW			SUNJ-100POTH			SUNJ-100PO			SUNJ-100SWUW
M type		SUNJ-125SW			SUNJ-125POTH			SUNJ-125PO			SUNJ-125SWUW

Flat

SR-SUS S type

Load capacity	150 kg
Platform size	440 x 740 mm
Usable size	440 x 740 mm
Suitable caster	SW/SWUW POTH/PO
Platform height	160 mm 160 mm
Empty weight	13.5 kg 13.1 kg

MR-SUS M type

Load capacity	300 kg
Platform size	560 x 860 mm
Usable size	560 x 860 mm
Suitable caster	SW/SWUW POTH/PO
Platform height	205 mm 205 mm
Empty weight	21.0 kg 19.8 kg



MR-SUS-SWUW (Option)

Plastic (Stainless Steel Type)

Single Ended with Folding Handle (Stainless Steel Type)

SA-SUG S type

Load capacity	200 kg
Platform size	460 x 750 mm
Usable size	460 x 680 mm
Suitable caster	SW/SWUW POTH/PO
Platform height	160 mm 160 mm
Handle height	870 mm 870 mm
Empty weight	12.0 kg 11.6 kg

MA-SUG M type

Load capacity	300 kg
Platform size	630 x 950 mm
Usable size	630 x 865 mm
Suitable caster	SW/SWUW POTH/PO
Platform height	205 mm 205 mm
Handle height	880 mm 880 mm
Empty weight	21.4 kg 20.2 kg



SA-SUG

Single Ended with Fixed Handle (Stainless Steel Type)

SB-SUG S type

Load capacity	200 kg
Platform size	460 x 750 mm
Usable size	460 x 700 mm
Suitable caster	SW/SWUW POTH/PO
Platform height	160 mm 160 mm
Handle height	860 mm 860 mm
Empty weight	11.0 kg 10.6 kg

MB-SUG M type

Load capacity	300 kg
Platform size	630 x 950 mm
Usable size	630 x 885 mm
Suitable caster	SW/SWUW POTH/PO
Platform height	205 mm 205 mm
Handle height	860 mm 860 mm
Empty weight	20.6 kg 19.4 kg



MB-SUG

Reference Number System

S	A	-	SUS	*Standard type: with Rubber wheels	SW
<small>S type</small>	<small>Folding Handle</small>		<small>Stainless Steel Platform</small>		
Please add reference No. of wheel as follows other than SW					
M	B	-	SUS	-	PO
<small>M type</small>	<small>Fixed Handle</small>		<small>Stainless Steel Platform</small>		<small>Wheel: PO</small>