

Extra Heavy Duty Casters

LS-GSPO Swivel casters

	Wheel diameter	Wheel width	Hub length	Total height	Plate dimensions	Bolt hole spacing	Bolt hole diameter	Axle bore diameter	Offset	Load capacity
LS-GSPO125K	125	55	60	170	140 × 110	105 × 75-80	11	12 (with steel bushes ϕ 25mm)	50	1750(17150)
LS-GSPO150K-35	150	55	60	205	175 × 140	140 × 105	14	16 (with steel bushes ϕ 30mm)	65	2500(24500)
LS-GSPO200K-35	200	55	60	255	175 × 140	140 × 105	14	16 (with steel bushes ϕ 30mm)	65	3000(29400)

※Color: Zinc plated yellow-passivated

LS-GSPO-ST Swivel with stopper

	Wheel diameter	Wheel width	Hub length	Total height	Plate dimensions	Bolt hole spacing	Bolt hole diameter	Axle bore diameter	Offset	Load capacity
LS-GSPO125K-ST	125	55	60	170	140 × 110	105 × 75-80	11	12 (with steel bushes ϕ 25mm)	50	1750(17150)
LS-GSPO150K-35-ST	150	55	60	205	175 × 140	140 × 105	14	16 (with steel bushes ϕ 30mm)	65	2500(24500)
LS-GSPO200K-35-ST	200	55	60	255	175 × 140	140 × 105	14	16 (with steel bushes ϕ 30mm)	65	3000(29400)

※Color: Zinc plated yellow-passivated

BS-GSPO Fixed casters

	Wheel diameter	Wheel width	Hub length	Total height	Plate dimensions	Bolt hole spacing	Bolt hole diameter	Axle bore diameter	Offset	Load capacity
BS-GSPO125K	125	55	60	170	140 × 110	105 × 75-80	11	12 (with steel bushes ϕ 25mm)	—	1750(17150)
BS-GSPO150K-35	150	55	60	205	175 × 140	140 × 105	14	16 (with steel bushes ϕ 30mm)	—	2500(24500)
BS-GSPO200K-35	200	55	60	255	175 × 140	140 × 105	14	16 (with steel bushes ϕ 30mm)	—	3000(29400)

※Color: Zinc plated yellow-passivated