

Twin Wheeled "Lift-lock" Casters

– with a unique height adjusting device

KP-50-U Swivel casters (polyurethane wheels)

	Wheel diameter	Wheel width	Hub length	Total height	Plate dimensions	Bolt hole spacing	Bolt hole diameter	Offset	Load capacity
KP-50B-U	50	12 × 2	46	70	54 × 54	42 × 42	6.5	12	40(390)
KP-50S-U	50	12 × 2	46	70	54 × 54	42 × 42	6.5	12	40(390)

KPB-50-U Swivel with stopper (polyurethane wheels)

	Wheel diameter	Wheel width	Hub length	Total height	Plate dimensions	Bolt hole spacing	Bolt hole diameter	Offset	Load capacity
KPB-50B-U	50	12 × 2	46	70	54 × 54	42 × 42	6.5	12	40(390)
KPB-50S-U	50	12 × 2	46	70	54 × 54	42 × 42	6.5	12	40(390)

KP-50-N Swivel casters (nylon wheels)

	Wheel diameter	Wheel width	Hub length	Total height	Plate dimensions	Bolt hole spacing	Bolt hole diameter	Offset	Load capacity
KP-50B-N	50	12 × 2	46	70	54 × 54	42 × 42	6.5	12	40(390)
KP-50S-N	50	12 × 2	46	70	54 × 54	42 × 42	6.5	12	40(390)

KPB-50-N Swivel with stopper (nylon wheels)

	Wheel diameter	Wheel width	Hub length	Total height	Plate dimensions	Bolt hole spacing	Bolt hole diameter	Offset	Load capacity
KPB-50B-N	50	12 × 2	46	70	54 × 54	42 × 42	6.5	12	40(390)
KPB-50S-N	50	12 × 2	46	70	54 × 54	42 × 42	6.5	12	40(390)

K-SJ-50-U Threaded stem fitting (polyurethane wheels)

	Wheel diameter	Wheel width	Hub length	Total height	Stem size	Offset	Load capacity
K-SJ-50B-U	50	12 × 2	46	65	M10 × 15 × P1.5	12	40(390)
K-SJ-50S-U	50	12 × 2	46	65	M10 × 15 × P1.5	12	40(390)

KB-SJ-50-U Threaded stem fitting with stopper (polyurethane wheels)

	Wheel diameter	Wheel width	Hub length	Total height	Stem size	Offset	Load capacity
KPB-50B-U	50	12 × 2	46	70	M10 × 15 × P1.5	12	40(390)
KPB-50S-U	50	12 × 2	46	70	M10 × 15 × P1.5	12	40(390)

K-SJ-50-N Threaded stem fitting (nylon wheels)

	Wheel diameter	Wheel width	Hub length	Total height	Stem size	Offset	Load capacity
K-SJ-50B-N	50	12 × 2	46	65	M10 × 15 × P1.5	12	40(390)
K-SJ-50S-N	50	12 × 2	46	65	M10 × 15 × P1.5	12	40(390)

KB-SJ-50-N Threaded stem fitting with stopper (nylon wheels)

	Wheel diameter	Wheel width	Hub length	Total height	Stem size	Offset	Load capacity
KPB-50B-N	50	12 × 2	46	70	M10 × 15 × P1.5	12	40(390)
KPB-50S-N	50	12 × 2	46	70	M10 × 15 × P1.5	12	40(390)