

# Pneumatic Wheel/Airless (Flat-free) Wheel Casters

## AIJ Swivel casters



AIJ-6-2G
AIJ-6 <sup>1</sup> / <sub>2</sub> x2-4
AIJ-2.00-4
AIJ-2.50-4
AIJ-3.00-4
AIJ-3.50-5

• Color: Zinc plated

## AILJ Swivel with airless tire



AILJ-2.50-4
AILJ-3.00-4
AILJ-3.50-5

## AIJB Swivel with stopper



AIJB-6-2G
AIJB-3.00-4

## SPMJ Swivel with semi-pneumatic tire



SPMJ-150
SPMJ-200

• Color: Zinc plated

## AIK Fixed casters



AIK-6-2G
AIK-6 <sup>1</sup> / <sub>2</sub> x2-4
AIK-2.00-4
AIK-2.50-4
AIK-3.00-4
AIK-3.50-5

• Color: Zinc plated

## AILK Fixed with airless tire



AILK-2.50-4
AILK-3.00-4
AILK-3.50-5

## AIKB Fixed with stopper



AIKB-6-2G
-----------

## SPMK Fixed with semi-pneumatic tire



SPMK-150
SPMK-200

• Color: Zinc plated

* Wheel diameter	* Wheel width	* Hub length	* Total height	Plate dimensions	Bolt hole spacing	Bolt hole diameter	Axle bore diameter	Offset	Load capacity	
mm	mm	mm	mm	mm	mm	mm	mm	mm	AI kg (N)	AIL kg (N)
153	47	56	198	120x120	90x90	11.5	20	41	70 (680)	—
166	52	87	231	140x140	112x112	11.5	20	58	70 (680)	—
204	52	87	246	140x140	112x112	11.5	20	58	80 (780)	—
220	60	90	287	160x160	125x125	14	20	71	85 (830)	100 (980)
248	76	90	304	160x160	125x125	14	20	71	110 (1070)	130 (1270)
290	92	109	374	175x175	140x140	14	25	71	160 (1560)	350 (3430)
150	45	56	198	120x120	90x90	11.5	20	45	80 (780)	—
200	45	56	250	140x140	112x112	11.5	20	58	100 (980)	—
153	47	56	198	137x93	100x56	11.5	20	20	70 (680)	—
166	52	87	231	151x100	112x63	11.5	20	20	70 (680)	—
204	52	87	246	151x100	112x63	11.5	20	20	80 (780)	—
220	60	90	287	200x140	140x80	14	20	20	85 (830)	100 (980)
248	76	90	304	200x140	140x80	14	20	20	110 (1070)	130 (1270)
290	92	109	374	220x150	160x90	14	25	25	160 (1560)	350 (3430)
150	45	56	198	137x93	100x56	11.5	20	20	80 (780)	—
200	45	56	250	151x100	112x63	11.5	20	20	100 (980)	—